

CONFiX™ WST split cable protection conduits

for cables with connectors



The CONFiX™ WST is a two piece corrugated conduit. Perfect for routing cables with or without connectors in rough environments.

In conjunction with e.g. KVT-W90, a high degree of flexibility is achieved. Numerous conduit sizes can be used thanks to the wide variety of split grommets offered.

The length of the CONFiX™ WST split corrugated conduit can be customized to your application. All conduits are available by the meter (0.5 m steps).

RoHS
compliant



Made in
Germany

Specifications

Material	Polypropylene
Operating temperature	-40 C° to 105 C°
Properties	UV-resistant

Advantages & benefits

■ Retrofits, repairs and maintenance can be done much more easily and quickly

Product types & sizes

CONFiX WST NW 10





Part No.	31200	Bending radius (static)	25 mm
EAN	4251269300066		
PU	1		
Length	50,000 mm		
Nominal size	NW 10		
External diameter	13.6 mm		
Internal diameter	8.7 mm		


CONFiX WST NW 14





Part No.	31210	Bending radius (static)	35 mm
EAN	4251269300073	Compatible with CONFiX FWS	31410, 31411
PU	1		
Length	50,000 mm		
Nominal size	NW 14		
External diameter	18.5 mm		
Internal diameter	12.5 mm		


	CONFiX WST NW 16	Part No.	31215	Bending radius (static)	40 mm
		EAN	4251269322471	Compatible with CONFiX FWS	31413, 31414
		PU	1		
		Length	50,000 mm		
		Nominal size	NW 16		
		External diameter	21.5 mm		
		Internal diameter	16 mm		

	CONFiX WST NW 20	Part No.	31220	Bending radius (static)	45 mm
		EAN	4251269300080		
		PU	1		
		Length	50,000 mm		
		Nominal size	NW 20		
		External diameter	25.5 mm		
		Internal diameter	19.5 mm		

	CONFiX WST NW 23	Part No.	31230	Bending radius (static)	50 mm
		EAN	4251269300097	Compatible with CONFiX FWS	31416, 31417
		PU	1		
		Length	50,000 mm		
		Nominal size	NW 23		
		External diameter	31 mm		
		Internal diameter	24.2 mm		

	CONFiX WST NW 29	Part No.	31235	Bending radius (static)	90 mm
		EAN	4251269319051	Compatible with CONFiX FWS	31419, 31420
		PU	1		
		Length	25,000 mm		
		Nominal size	NW 29		
		External diameter	35.5 mm		
		Internal diameter	27.3 mm		

	CONFiX WST NW 37	Part No.	31240	Bending radius (static)	110 mm
		EAN	4251269300103	Compatible with CONFiX FWS	31422, 31423
		PU	1		
		Length	25,000 mm		
		Nominal size	NW 37		
		External diameter	41.4 mm		
		Internal diameter	31 mm		

	CONFiX WST NW 45	Part No.	31250	Bending radius (static)	130 mm
		EAN	4251269300110	Compatible with CONFiX FWS	31425, 31426
		PU	1		
		Length	25,000 mm		
		Nominal size	NW 45		
		External diameter	54 mm		
		Internal diameter	42.7 mm		

CONFIX WST NW 70



Part No.	31260
EAN	4251269300127
PU	1
Length	10,000 mm
Nominal size	NW 70
External diameter	79.8 mm
Internal diameter	66.5 mm

Bending radius (static)

190 mm

□