


Art.no. 51743



39° Touch		
m	Ø	Lux
1,0	0,7	5631
2,0	1,4	1408
3,0	2,2	626
4,0	2,9	352

LED 3000 lm 930



Touch is a stylish and timeless luminaire that will fit smoothly into any retail environment. The integrated driver gives clean feeling and the shop ceiling will not be cluttered with drivers aimed in different directions.

Installation Track mounted 3-phase track, Control track or iTrack.

Design Housing in powder coated aluminium, white (RAL 9016), black (RAL 9017) or grey (RAL 7038). Integrated driver.

Dimming DALI/phase pulse control

Miscellaneous 930 LED is Below Black Body Locus (BBBL), other colour temperature on Black Body Locus.

Touch Midi

Wide Beam, 3-phase track, BBBL

DESIGN

Colour Grey RAL 7038
Weight, kg 1.2

TECHNICAL DATA

Installation 3-phase track Protection class 1
IP rating 20

ELECTRICAL DATA

Rated supply voltage, V 230 Effect, W 31

LIGHTING DATA

Light distribution Wide Beam Lumen output 3158
lm/W 102 Lumen maintenance L90 B50, h 100 000
LED driver, h/max failure % 50 000 /10 SDCM 3
CRI 90 CCT, K 3000
Light source LED Beam angle, ° 40°