Rittal – The System.

Faster – better – everywhere.



SV 9686.030

Busbar support

State: 06/07/2022 (Source: rittal.com/com-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

SV 9686.030 - Busbar support for busbar baying (roof section)

For baying busbar systems from enclosure to enclosure in the roof section.

Features

Model No.	SV 9686.030
Product description	For baying 3- or 4-pole flat copper busbar systems from enclosure to enclosure in the roof section.
Material	Duroplastic Fire protection corresponding to UL 94-V0
Colour	Similar to RAL 9005
Supply includes	Assembly parts
To fit busbars	50 x 10
Centre-to-centre spacing of busbars	80 mm
Assembly instruction	For the installation of max. 4 busbars (sub-conductors) per phase Cage nut (M8) 4165.500 is required to attach the busbar support to the enclosure section
Packs of	2 pc(s).
Weight/pack	3.5 kg
Copper weight (kg per piece)	0
Customs tariff number	85469010
EAN	4028177935655
ETIM 7.0	EC001166
ECLASS 8.0	27400607

© Rittal 2022

Approvals

Approvals	DNV-GL UL + C-UL
Explanations	Declaration of conformity Declaration of conformity UK