

# KEL-DPZ-E Cable Entry Plates





Conical shape on back provides additional sealing and strain relief



Also available in black.



Description	Type	Order No.	Number of cables	PU
	KEL-DPZ-E 112 7	<span style="background-color: #cccccc; border: 1px solid black; padding: 2px;">43780</span> <span style="background-color: #333333; color: white; border: 1px solid black; padding: 2px;">50780</span>	7 × 7.5 - 12 mm / 0.295 - 0.472 "	10
	KEL-DPZ-E 112 21	<span style="background-color: #cccccc; border: 1px solid black; padding: 2px;">43790</span> <span style="background-color: #333333; color: white; border: 1px solid black; padding: 2px;">50790</span>	21 × 3.2 - 6.5 mm / 0.126 - 0.248 "	10

\* Only valid for gray product types

## Product Description

KEL-DPZ-E is designed for routing cables without connectors in very small space.

The assembly of the KEL-DPZ-E with cables or pneumatic hoses can be done quick and easy. Simply make a small hole in the thin membrane, push the cables through. The KEL-DPZ-E provides strain relief and protection IP66 / UL type 12.

With an area of only 18 × 112 mm, up to 21 cables can be easily routed and sealed.

ST-B Plugs can be used for sealing pierced membranes if cables have been removed.

## Advantages & Benefits

- Space saving shape
- Dual sealing of cables acc. to IP66/UL type 12
- High cable density
- Fast and easy assembly
- Hygienic design

## Specifications

Material	Frame: Polyamide (PA) Sealing plate: Elastomer
Color	<span style="background-color: #cccccc; border: 1px solid black; padding: 2px;"> </span> gray (similar RAL 7035) <span style="background-color: #333333; color: white; border: 1px solid black; padding: 2px;"> </span> black
Flame class	UL94-Vo
IP rating	IP66 (certified acc. to EN 60529)
UL type rating	UL type 12 (acc. to UL 50E)
Operating temperature	- 40°C to + 100°C (static) - 40°F to + 212°F (static)
Properties	Halogen-free, silicone-free
Cut-out dimensions	18 × 112 mm / page 220 - 221
Plate depth	14 mm / 0.551 "

## Accessories

ST-B Plugs	93
KEL-EMC-PF Grounding mounts	149