



OFF switch 32 A 2 NO Terminal 6 mm<sup>2</sup>

Model	
product brand name	SETRON
product designation	On/Off switches
design of the product	2 NO
design of the switching function	Off switches
General technical data	
number of poles	1
short-circuit current rating	10 kA
type of voltage / of the operating voltage	AC
Supply voltage	
operating voltage / rated value	400 V
Protection class	
protection class IP	Other
Switching capacity	
switching capacity current / rated value	0.096 kA
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	0.7 W
Main circuit	
operational current / rated value	32 A
Product details	
product component / signal lamp	No
number of NO contacts	2
Product function	
product function / positive opening (acc. to DIN VDE 0113)	No
connectable conductor cross-section / for flexible conductor / with core end processing	
• minimum	1 mm <sup>2</sup>
• maximum	6 mm <sup>2</sup>
connectable conductor cross-section / for rigid conductor	
• minimum	1 mm <sup>2</sup>
• maximum	6 mm <sup>2</sup>
tightening torque / with screw-type terminals	
• minimum	0.8 N·m
• maximum	1 N·m
Mechanical Design	
height	90 mm

depth	77 mm
installation depth	70 mm
number of modular width units	1
net weight	75 g
ambient temperature / during operation	
• minimum	-5 °C
• maximum	40 °C
ambient temperature / during storage / minimum	-25 °C
<b>General Product Approval</b>	
<b>Declaration of Conformity</b>	
<b>Test Certificates</b>	



[Miscellaneous](#)

[Type Test Certificates/Test Report](#)

**other**

[Miscellaneous](#)

[Environmental Conformations](#)

**Further information**

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TE8212>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5TE8212>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5TE8212](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TE8212)

**CAx-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

