



INSTA contactor with 1 NO contact and 1 NC contact Contact for 230 V AC, 400V 20A Control 230 V AC

Model	
product brand name	SETRON
product designation	Insta contactor
design of the product	1 NO contact 1 NC contact
type of voltage / of the operating voltage	AC
type of voltage / of the operating voltage / for actuation	AC
Supply voltage	
operating voltage / rated value	
• minimum	250 V
• maximum	250 V
Protection class	
protection class IP	IP20
Switching capacity	
switching capacity active power / with incandescent lamp load	1 000 W
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	1.7 W
Current	
operational current / at AC / rated value	20 A
Main circuit	
operational current / rated value	20 A
Control current	
control supply voltage	
• rated value	230 V
• rated value / maximum	230 V
Product details	
product component / slide for manual operation	No
number of NC contacts	1
number of NO contacts	1
product extension / installable / supplementary devices	Yes
Mechanical Design	
height	90 mm
width	18 mm
depth	71 mm
installation depth	0 mm
number of modular width units	1

net weight

141 g

General Product Approval

Declaration of
Conformity

Test Certificates



[Miscellaneous](#)

[Miscellaneous](#)



[Special Test Certificate](#)

other

[Confirmation](#)

[Miscellaneous](#)

[Environmental Confirmations](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TT5801-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TT5801-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5TT5801-0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

