

DELTA i-system carbon metallic SCHUKO socket outlet 10/16 A 250 V With screwless Connection terminals with spring flap 55x 55 mm and increased touch protection



Model	
Cover version	central plate
Design of the special power supply unit	without special current supply
Design of the socket / according to VDE 0620 for severe conditions	No
Design of the phase tap	No
General technical data	
Marking / of socket outlet	without imprint
Mounting type	fixing with claw and screw
Surface processing	others
Material	thermoplastic
Supply voltage	
Operating voltage / Rated value	250 V
Protection class	
Protection class IP	IP20
Main circuit	
Operating current / Rated value	16 A

Appearance

Color miscellaneous

Product details

Product component

- Ejection equipment No
- Labeling field No
- Increased touch protection Yes
- Fault current protection No
- miniature fuse No
- Integrated / functional lighting No
- Integrated / Light source No
- Integrated / orientation lighting No
- Hinged lid Yes

Product feature

- lockable No
- halogen-free Yes
- transparent No

Product function

Product function

- Socket selectable No
- Overvoltage protection No

Number

Number of units 1

Number of sockets / switchable 0

Connections

Arrangement of contacts / diagonal No

Type of electrical connection plug terminal

Mechanical Design

Height 70 mm

Width 70 mm

Depth 45 mm

Mounting type flush mounted

Material / of the enclosure plastic

Certificates



ÖVE



VDE



EG-Konf.

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5UB1920>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/5UB1920>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5UB1920**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>