

SIMATIC ET 200SP, BaseUnit BU15-P16+A0+2D, BU type A0,
 Push-in terminals, without AUX terminals, New load group, WxH: 15x
 117 mm



Figure similar

General information	
Product type designation	BU type A0
HW functional status	From FS06
Supply voltage	
Rated value (DC)	24 V
external protection for power supply lines	Yes; 24 V DC/10 A miniature circuit breaker with type B or C tripping characteristic
Mains filter	
<ul style="list-style-type: none"> integrated 	Yes
Current carrying capacity	
For P1 and P2 bus, max.	10 A
For process terminals, max.	2 A
Hardware configuration	
Formation of potential groups	
<ul style="list-style-type: none"> New potential group 	Yes
<ul style="list-style-type: none"> Potential group continued from the left 	No

Potential separation	
between the potential groups	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. 	-30 °C 60 °C -30 °C 50 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. 	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Accessories	
Color coding labels	
<ul style="list-style-type: none"> for process terminals for AUX terminals for add-on terminals 	CC00 to CC09 does not exist does not exist
Connection method	
Terminals	
<ul style="list-style-type: none"> Terminal type Conductor cross-section, min. Conductor cross-section, max. Number of process terminals to I/O module Number of terminals to AUX bus Number of add-on terminals Number of terminals with connection to P1 and P2 bus 	Push-in terminal 0.14 mm ² ; AWG 26 2.5 mm ² ; AWG 14 16 0 0 2
Dimensions	
Width	15 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	40 g
last modified:	11/14/2019