

SIMATIC S7-1500 Digital input/output module, DI16x 24 V DC BA, 16 channels in groups of 16, Input delay typ. 3.2 ms Input type 3 (IEC 61131), DQ16X24 V DC/0.5A BA; 16 channels in groups of 8; 4 A per group; Delivery incl. front connector Push-in



General information	
Product type designation	DI 16x24VDC / DQ16x24VDC/0.5A BA
HW functional status	FS01
Firmware version	V1.0.0
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Prioritized startup</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated as of version</li> </ul>	V13 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated as of version</li> </ul>	V5.5 SP3 / -
<ul style="list-style-type: none"> <li>PROFIBUS as of GSD version/GSD revision</li> </ul>	V1.0 / V5.1
<ul style="list-style-type: none"> <li>PROFINET as of GSD version/GSD revision</li> </ul>	V2.3 / -
Operating mode	
<ul style="list-style-type: none"> <li>DI</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Counter</li> </ul>	No
<ul style="list-style-type: none"> <li>DQ</li> </ul>	Yes
<ul style="list-style-type: none"> <li>DQ with energy-saving function</li> </ul>	No

• PWM	No
• Oversampling	No
• MSI	Yes
• MSO	Yes

#### Supply voltage

Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes; through internal protection with 7 A per group

#### Input current

Current consumption, max.	30 mA
---------------------------	-------

#### Output voltage

Rated value (DC)	24 V
------------------	------

#### Power

Power available from the backplane bus	1.1 W
--	-------

#### Power loss

Power loss, typ.	3.45 W
------------------	--------

#### Digital inputs

Number of digital inputs	16
Digital inputs, parameterizable	No
Source/sink input	P-reading
Input characteristic curve in accordance with IEC 61131, type 3	Yes

#### Input voltage

• Rated value (DC)	24 V
• for signal "0"	-30 to +5 V
• for signal "1"	+11 to +30V

#### Input current

• for signal "1", typ.	2.7 mA
------------------------	--------

#### Input delay (for rated value of input voltage)

##### for standard inputs

— parameterizable	No
— at "0" to "1", min.	3 ms
— at "0" to "1", max.	4 ms
— at "1" to "0", min.	3 ms
— at "1" to "0", max.	4 ms

##### for interrupt inputs

— parameterizable	No
-------------------	----

#### Cable length

• shielded, max.	1 000 m
------------------	---------

- unshielded, max.

600 m

## Digital outputs

Type of digital output	Transistor
Number of digital outputs	16
Current-sourcing	Yes
Digital outputs, parameterizable	No
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	1 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Controlling a digital input	Yes
<b>Switching capacity of the outputs</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	5 W
<b>Load resistance range</b>	
<ul style="list-style-type: none"> <li>• lower limit</li> </ul>	48 Ω
<ul style="list-style-type: none"> <li>• upper limit</li> </ul>	12 kΩ
<b>Output voltage</b>	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ (-0.8 V)
<b>Output current</b>	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul>	0.5 A
<ul style="list-style-type: none"> <li>• for signal "0" residual current, max.</li> </ul>	0.5 mA
<b>Output delay with resistive load</b>	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>	100 μs
<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	500 μs
<b>Parallel switching of two outputs</b>	
<ul style="list-style-type: none"> <li>• for logic links</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>	Yes
<b>Switching frequency</b>	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>	0.5 Hz
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	10 Hz
<b>Total current of the outputs</b>	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> </ul>	0.5 A; see additional description in the manual
<ul style="list-style-type: none"> <li>• Current per group, max.</li> </ul>	4 A; see additional description in the manual
<ul style="list-style-type: none"> <li>• Current per module, max.</li> </ul>	8 A; see additional description in the manual
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m

## Encoder

Connectable encoders	
<ul style="list-style-type: none"> <li>• 2-wire sensor</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— permissible quiescent current (2-wire sensor), max.</li> </ul>	1.5 mA
Interrupts/diagnostics/status information	
Diagnostics function	No
Substitute values connectable	No
Alarms	
<ul style="list-style-type: none"> <li>• Diagnostic alarm</li> </ul>	No
<ul style="list-style-type: none"> <li>• Maintenance interrupt</li> </ul>	No
<ul style="list-style-type: none"> <li>• Hardware interrupt</li> </ul>	No
Diagnostic messages	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> </ul>	No
<ul style="list-style-type: none"> <li>• Wire-break</li> </ul>	No
<ul style="list-style-type: none"> <li>• Short-circuit</li> </ul>	No
<ul style="list-style-type: none"> <li>• Group error</li> </ul>	No
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>• RUN LED</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>• ERROR LED</li> </ul>	Yes; red LED
<ul style="list-style-type: none"> <li>• Monitoring of the supply voltage (PWR-LED)</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>• Channel status display</li> </ul>	Yes; green LED
<ul style="list-style-type: none"> <li>• for channel diagnostics</li> </ul>	No
<ul style="list-style-type: none"> <li>• for module diagnostics</li> </ul>	No
Potential separation	
Potential separation channels	
<ul style="list-style-type: none"> <li>• between the channels</li> </ul>	No
<ul style="list-style-type: none"> <li>• between the channels, in groups of</li> </ul>	8
<ul style="list-style-type: none"> <li>• between the channels and backplane bus</li> </ul>	Yes
Isolation	
Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>• horizontal installation, min.</li> </ul>	0 °C
<ul style="list-style-type: none"> <li>• horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>• vertical installation, min.</li> </ul>	0 °C
<ul style="list-style-type: none"> <li>• vertical installation, max.</li> </ul>	40 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> <li>• Installation altitude above sea level, max.</li> </ul>	5 000 m; Restrictions for installation altitudes > 2 000 m, see manual
Dimensions	

Width	25 mm
Height	147 mm
Depth	129 mm

#### Weights

Weight, approx.	280 g
-----------------	-------

#### Other

Note:	Supplied incl. 40-pole push-in front connectors
-------	---

<b>last modified:</b>	02/03/2020
-----------------------	------------