



## Art.no.: 17489-402



## Gondol LED

DALI/Phase-pulse

### DESIGN

Colour	White	Width, mm	142
RAL	9016	Height, mm	50
Weight, kg	2.8	Module	1200
Length, mm	1192		

### TECHNICAL DATA

IP rating	20	Light control	DALI/Phase-pulse
-----------	----	---------------	------------------

### ELECTRICAL DATA

Effect, W 20

### LIGHTING DATA

Lumen output	2984	SDCM	3
lm/W	146	CRI	80
Lumen maintenance L90 B10, h	50 000	CCT, K	4000
Lumen maintenance at 50 000 h	0,92	Light source	LED
LED driver, h/max failure %	100 000/10 %		

**A recessed luminaire for suspended ceilings with visible T-bars. The luminaire creates even, glare-free, vertical lighting to achieve good visual comfort.**

**Installation** Recessed mounting – recessed mounting in suspended ceilings with visible T-bars. Also approved for recessed mounting in ventilated areas.

**Connection** 5-way snap-in terminal block on top of the luminaire.

**Design** White enamelled sheet steel (RAL 9016).

**Louvre** The lightsource is concealed in the luminaire and hidden from view with standard installation.

**Reflector** Metallised aluminium with satin matt finish. Asymmetrical light distribution for lighting of vertical areas.

**Dimming** DALI as standard.